

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: SA-8 BATTERY CLEANER 5 OZ AE
Item No: 80369
Product Type: Aerosol cleaner

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
WATER 7732-18-5	>75	Not listed	Not listed
BUTANE 106-97-8	<7	1000 ppm	800 ppm; 1900 mg/m ³
2-BUTOXYETHANOL 111-76-2	<5	20 ppm	50 ppm; 240 mg/m ³
PROPANE 74-98-6	<5	1000 ppm	1000 ppm; 1800 mg/m ³

3. HAZARDS IDENTIFICATION

Toxicity: Exposure to 2-butoxyethanol can cause nausea, dizziness, vomiting, malaise, incoordination, diarrhea, weakness, eye redness and swelling of conjunctiva.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. May cause pain, redness or swelling of the eyes and excessive blinking and tear production. Skin: Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying, cracking and skin burns. Preexisting skin disorders may be aggravated by exposure. Skin absorption is possible, but harmful effects are not expected from this route under normal conditions of handling and use.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
2-BUTOXYETHANOL 111-76-2	<5	male rat-no evidence; female rat-equivocal evidence; male mice- some evidence; female mice-some evidence	A3	Group 3; Monograph 88, 2006

Medical Conditions Recognized as Being Aggravated by Exposure: Persons with preexisting respiratory, liver, kidney, eye or skin diseases may be adversely affected.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. If not breathing, give artificial respiration. Obtain medical attention.
Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): No flame projection
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

5. FIRE FIGHTING MEASURES

Hazardous Products of Combustion:
Unusual Fire/Explosion Hazards:

Oxides of carbon
 Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Keep containers cool. Use equipment or shielding to protect personnel from bursting containers.

Lower Explosive Limit:
Upper Explosive Limit:

Not determined
 Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).

Handling:

Avoid contact with skin and eyes. Do not inhale vapors. Do not use near heat, sparks or open flame. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses.

Skin:

Neoprene or nitrile gloves recommended.

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection:

An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

White foam

Odor:

Solvent

Boiling Point:

>200°F

pH:

7.5-8.5

Solubility in Water:

Soluble

Specific Gravity:

0.95-1.05

VOC(Wt.%):

13%

Vapor Pressure:

Not determined

Vapor Density (Air=1):

>1

Evaporation Rate:

<1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Strong oxidizers

Conditions to Avoid:

Keep away from heat, sparks and open flame.

Hazardous Products of Combustion:

Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:

Disposal should be made in accordance with federal, state and local regulations.. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

US EPA Waste Number:

D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Ground Transport (DOT)

14. TRANSPORTATION INFORMATION

DOT Shipping Name: Consumer Commodity (not more than one liter)
Hazard Class: ORM-D
UN/ID Number: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)
Class or Division: Class 9
UN/ID Number: ID 8000

IMDG

Proper Shipping: Aerosols, Limited Quantity
Hazard Class: Class 2.2
UN Number: UN 1950

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

2-Butoxyethanol

California Proposition 65: WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 2, REACTIVITY 0.
Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 2, PHYSICAL HAZARD 0
NFPA is a registered trademark of the National Fire Protection Assn.
HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: January 22, 2010
Revision Number: 2

Telephone No.: 1-87-Permatex (877) 376-2839