

Permatex Europe
 Unit 3, Express Park,
 Shipton Way, Northampton Road,
 Rushden, Northamptonshire
 NN10 6GK UK
 Ph: 0870 4589545

SAFETY DATA SHEET
 according to REACH regulation 1907/2006

1. IDENTIFICATION OF THE PREPARATION

Identification of the preparation: **26BR HIGH TEMP RTV RED SILICONE GASKET MAKER 3 OZ**
 Item No: **81160**
 Recommended use: **Silicone elastomer**

2. HAZARDS IDENTIFICATION

Classification: Xi - Irritant
Most Important Hazards: Irritating to eyes and skin. Irritating to mouth, throat and stomach. When this product is exposed to moisture, acetic acid may be formed. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	EC Number	EU Classification
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	>60	Not determined	None
AMORPHOUS SILICA 7631-86-9	5-15	231-545-4	None
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	<7	265-148-2	Carc. Cat.2;R45 Nota N N:R51/53
IRON OXIDE 1309-37-1	<5	215-168-2	None
ETHYLTRIACETOXSILANE 17689-77-9	<5	241-677-4	C;R34 Xn;R22 R14
METHYLTRIACETOXSILANE 4253-34-3	<5	224-221-9	C;R34 Xn;R22 R14
POLYDIMETHYLSILOXANE 63148-62-9	<5	Not determined	None
TITANIUM DIOXIDE 13463-67-7	<2	236-675-5	None
ACETIC ACID 64-19-7	0.5-2.0	200-580-7	C;R35 R10

4. FIRST-AID MEASURES

General advice: If you feel unwell, seek medical advice (show the label where possible).
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.

4. FIRST-AID MEASURES

Skin Contact: Wipe off material with paper towel or cloth. Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Ingestion: Rinse mouth. If swallowed, seek medical advice immediately and show this container or label.

Protection of first-aiders: Use personal protective equipment. Avoid contact with skin, eyes and clothing.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Carbon dioxide (CO2), Dry chemical, foam

Extinguishing media which must not be used for safety reasons: None reasonably foreseeable.

Special instructions for protection and hygiene: Thermal decomposition can lead to release of irritating gases and vapours.

Special protective equipment for firefighters: Use personal protective equipment. Avoid contact with eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: For additional information on processing see sections 7, 8 and 11 of this safety data sheet.

Environmental Precautions: Do not flush into surface water or sanitary sewer system.

Cleanup: Scrape up. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Slippery, can cause falls if walked on.

7. HANDLING AND STORAGE

Handling precautions: Avoid breathing vapors or mists. Avoid contact with the skin and the eyes. Do not ingest. Wash hands before breaks and immediately after handling the product.

Storage: Store in cool place. Keep containers dry and tightly closed to avoid moisture absorption and contamination.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Component	ACGIH; TLV-TWA	German MAK; TWA	UK WEL; TWA	Finnish OEL; HTP
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	Not listed	Not listed	Not listed	Not listed

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Component	ACGIH; TLV-TWA	German MAK; TWA	UK WEL; TWA	Finnish OEL; HTP
AMORPHOUS SILICA 7631-86-9	10 mg/m ³	4 mg/m ³	6 mg/m ³	Not listed
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	5 mg/m ³	Not listed	Not listed	Not listed
IRON OXIDE 1309-37-1	5 mg/m ³ (Fe)	1.5 mg/m ³	5 mg/m ³	8h: 5 mg/m ³
ETHYLTRIACETOXSILANE 17689-77-9	Not listed	Not listed	Not listed	Not listed
METHYLTRIACETOXSILAN E 4253-34-3	Not listed	Not listed	Not listed	Not listed
POLYDIMETHYLSILOXANE 63148-62-9	Not listed	Not listed	Not listed	Not listed
TITANIUM DIOXIDE 13463-67-7	10 mg/m ³	1.5 mg/m ³	10 mg/m ³	Not listed
ACETIC ACID 64-19-7	10 ppm	10 ppm; 25 mg/m ³	Not listed	8h: 5 ppm, 13 mg/m ³ ; 15min: 10 ppm, 25 mg/m ³

Ventilation: Provide adequate ventilation .
Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.
Skin: Neoprene or nitrile gloves recommended.
Eyes: Safety glasses
Hygiene Measures: When using, do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Red paste
Odor: Acetic acid
pH: Does not apply
Boiling point/range: polymerization
Melting point: Not determined
Flash point: >95°C
Risk of explosion: None reasonably foreseeable.
Vapor pressure: <5 mm Hg
Density: 1.05
Solubility in water: polymerization
Partition coefficient (n-octanol/water): Not determined
Vapor density: >1 (Air = 1)
Evaporation Rate: Not determined
VOC Content(%): 4.6%

10. STABILITY/REACTIVITY

Stability: Stable under normal conditions.
Conditions to Avoid: Exposure to moisture
Materials to avoid: Polymerization can occur, Water, Acids, Strong oxidizing agents
Hazardous decomposition products: Carbon oxides, nitrogen oxides (NOx), acetic acid, formaldehyde

11. TOXICOLOGICAL INFORMATION

Component	Weight%	LD50/oral/rat	LC50/inhalation/rat
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	>60	>40,000 mg/kg	>535 mg/l
AMORPHOUS SILICA 7631-86-9	5-15	>5000 mg/kg	>2.2 mg/L/1H
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	<7	7400 mg/kg	4.6 mg/L/4H
IRON OXIDE 1309-37-1	<5	>10000 mg/kg	
METHYLTRIACTOXSILANE 4253-34-3	<5	2060 mg/kg	
POLYDIMETHYLSILOXANE 63148-62-9	<5	>17 g/kg	
TITANIUM DIOXIDE 13463-67-7	<2	>10000 mg/kg	
ACETIC ACID 64-19-7	0.5-2.0	3310 mg/kg	11.4 mg/L/1H

Local Effects

Skin Irritation:

May cause skin irritation and/or dermatitis.

Eye Irritation:

Irritating, but will not permanently injure eye tissue.

Inhalation:

May cause irritation of respiratory tract. May cause irritation of the mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Note: This product does not contain microcrystalline silica.

Ingestion:

Irritating to mouth, throat and stomach.

Sensitization:

None reasonably foreseeable.

Chronic toxicity:

None reasonably foreseeable

Specific Effects

Carcinogenic effects:

May form formaldehyde at high temperatures.

Mutagenic effects:

None reasonably foreseeable.

Reproductive toxicity:

None reasonably foreseeable

Target Organ Effects:

Eyes, Gastrointestinal Tract, Respiratory System, Skin

12. ECOLOGICAL INFORMATION

Ecotoxicity:

May cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

Waste from Residues:

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

RoHS/WEEE:

This product is in compliance with EU Directive 2002/95/EC Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment (RoHS) and EU Directive 2002/96/EC Restriction on waste electrical and electronic equipment (WEEE).

14. TRANSPORT INFORMATION

IATA

Proper Shipping Name: Not regulated

Hazard Class: Not applicable

UN/ID No: Not applicable

IMDG

Proper shipping name: Not applicable

Hazard Class: Not applicable

Product Name: 26BR HIGH TEMP RTV RED SILICONE
GASKET MAKER 3 OZ

Item No: 81160

14. TRANSPORT INFORMATION

UN/ID No: Not applicable
Marine Pollutant: None

ADR/RID

Proper Shipping Name: Not regulated
Hazard Class: Not applicable
UN/ID No: None

15. REGULATORY INFORMATION

This product is classified in accordance with Annex VI to Directive 67/548/EEC

Suspect cancer is not applicable - Refer to Section 2.

Indication of Danger:

Xi - Irritant

R -phrase(s):

R36/38 - Irritating to eyes and skin

R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

S -phrase(s):

S 2 - Keep out of the reach of children

S24/25 - Avoid contact with skin and eyes

S37 - Wear suitable gloves

S51 - Use only in well-ventilated areas

S61 - Avoid release to the environment. Refer to special instructions/safety data sheets

16. OTHER INFORMATION

Risk Phrases mentioned in Section 2:

R10 - Flammable.

R14 - Reacts violently with water.

R22 - Harmful if swallowed.

R34 - Causes burns.

R35 - Causes severe burns.

R45 - May cause cancer.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Prepared By: Denise Boyd, Manager-
Environmental, Health & Safety

Company: Permatex. Inc. 10 Columbus
Blvd. Hartford, CT USA 06106

Telephone: 877-376-2839

Revision Date: December/14/2006

Revision Number: 6