

SELECT DIESEL SAE 15W40

11236

Supplier ACDelco Europe Paseo de la Castellana 91 28040 Madrid	
fax; +34 91456 9288 Anti-poison centre +32 (0)70 245 2	245
1. Identification of the product and	
Identification of the product Use Company identification	: Oily liquid.: Automobile industry: See distributor.
2. Information on ingredients	
 This product is not considered to b Substance name Polyolefin polyamine succinimide, : Polyol 	be hazardous but contains hazardous components. Value(s) CAS nr / EINECS nr / EC index Symbol(s) R-Phrase(s) ca 1.49 % / 53
3. Hazards identification	
Symptoms relating to use - Inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
- Skin contact	 Not expected to present a significant skin hazard under anticipated conditions of normal use.
- Eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
- Ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.
4. First aid measures	
First aid - Inhalation - Skin contact - Eye contact - Ingestion	 Not expected to require first aid measures. Wash skin thoroughly with mild soap and water. In case of eye contact, immediately rinse with clean water for 10-15 minutes. DO NOT INDUCE VOMITING.
-	Rinse mouth. Seek medical attention immediately.
5. Fire - fighting measures	
Prevention Extinguishing media	 No smoking. Foam. Dry chemical. Carbon dioxide.
Special procedures	: Exercise caution when fighting any chemical fire.
6. Accidental release measures	
Personal precautions After spillage and/or leakage	No smoking.Spill area may be slippery. Dike for recovery or absorb with appropriate material. Use suitable disposal containers.



SELECT DIESEL SAE 15W40

Page: 2

Revision nr: 2

Date : 17/2/2004 Supersedes : 4/8/2003

11236

_				
7	Hand	lina	and	storage
	- Tarra	g	ana	Juliage

General	: No naked flames. No smoking.
Storage	: Keep at temperature not exceeding 40°C Store in dry, well-ventilated area.
Handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking or when leaving work.
Transport temperature	: Keep at temperature not exceeding 40°C

8. Exposure controls / personal protection

Personal protection

-	Respiratory	protection

- Skin protection

- Eye protection

- Ingestion

Industrial hygiene

- **Occupational Exposure Limits**
- : No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation.
- : No special clothing/skin protection equipment is recommended under normal conditions of use.
- : Goggles.
 - : When using, do not eat, drink or smoke.
 - : No special protection required where adequate ventilation is maintained.
 - : 5 mg/m3 for oil mists (TWA, 8h-workday) recommended, based upon the ACGIH TLV (Analysis according to US NIOSH Method 5026, NIOSH Manual of Analytical Methods, 3rd Edition).

9. Physical and chemical properties

	Physical state	: Oily liquid.
	Colour	: Yellow-brown.
	Odour	: Oil.
*	pH value	: Not applicable.
	Density [g/dm ³]	: 880
*	Vapour density (101.3 kPa/air=1)	: >12
	Viscosity at 40°C [mm2/s]	: 105
	Solubility in water	: Negligible.
	Flash point [°C] (ASTM D 92)	: >230
*	Auto-ignition temperature [°C]	: No data available.
	Explosion limits (vol% in air)	: LEL: 1.0 UEL: 6.0
*	Log P octanol / water at 20°C	: No data available.

Log P octanol / water at 20°C

10. Stability and reactivity

Hazardous decomposition products	: None under normal conditions.
Hazardous reactions	: None under normal conditions.
Hazardous properties	: None under normal conditions.
Materials to avoid	: Strong oxidizers. Acids. Bases.

11. Toxicological information		
Rat oral LD50 [mg/kg]	: No data available.	
Inhalation	 Neglegible hazard at ambient/normal handling temperatues. Elevated temperatures or mechanical action may form vapours, mists, or fumes, which may be irritating to the nose, throat and lungs. 	
Skin contac	: Repeated or prolonged skin contact may cause irritation.	
Eye contact	: Slightly irritant, does not damage eye tissue	



MATERIAL SAFETY DATA SHEET

SELECT DIESEL SAE 15W40

Revision nr : 2 Date : 17/2/2004

Page : 3

Supersedes : 4/8/2003

11236

11. Toxicological information (continued)		
Ingestion	: Low level of acute/systematic toxicity. Minute amounts aspirated into the lungs during ingestion or vomiting may cause severe pulmonary injury and death.	
12. Ecological information		
* Persistence and degradability	: Not soluble in water, so only minimally biodegradable.	
13. Disposal considerations		
Disposal	: Dispose in a safe manner in accordance with local/national regulations.	
14. Transport information		
General information	: Not regulated.	
15. Regulatory information		
Symbol(s) R Phrase(s) S Phrase(s) * Safety advises	 None. None. None. Contains : LOB Calcium long chain alkarylsulphonate. May produce an allergic reaction. 	
16. Other information		
Text of R-Phrases in § 2 Further information Print date	 R53 - May cause long-term adverse effects in the aquatic environment. Revision - See : * 5/4/2004 	

DISCLAIMER OF LIABILITY The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document