

# MATERIAL SAFETY DATA SHEET

Page : 1
Revision nr : 2

Date : 5/4/2004 Supersedes : 3/10/2003

11237

## **SELECT PETROL & DIESEL 15W50**

Supplier ACDelco Europe Paseo de la Castellana 91 28040 Madrid

fax; +34 91456 9288 Anti-poison centre +32 (0)70 245 245

#### 1. Identification of the product and the company

Identification of the product : Oily liquid.

Use : Automobile industry Company identification : See distributor.

#### 2. Information on ingredients

\* This product is not considered to be hazardous but contains hazardous components.

Substance name Value(s) CAS nr / EINECS nr / EC index Symbol(s) R-Phrase(s)

Polyolefin polyamine succinimide. : ca 1.49 ----- / ----- 53

<u>Polyol</u>

#### 3. Hazards identification

Symptoms relating to use

- Inhalation : Not expected to present a significant inhalation hazard under anticipated conditions

of normal use.

- Skin contact : Not expected to present a significant skin hazard under anticipated conditions of

normal use.

- Eye contact : Not expected to present a significant eye contact hazard under anticipated

conditions of normal use.

- Ingestion : Not expected to present a significant ingestion hazard under anticipated conditions

of normal use.

#### 4. First aid measures

First aid

InhalationSkin contactNot expected to require first aid measures.Wash skin thoroughly with mild soap and water.

- Eye contact : In case of eye contact, immediately rinse with clean water for 10-15 minutes.

- Ingestion : DO NOT INDUCE VOMITING.

Rinse mouth.

Seek medical attention immediately.

#### 5. Fire - fighting measures

Prevention : No smoking.

Extinguishing media : Foam.

Dry chemical.

Carbon dioxide.

Special procedures : Exercise caution when fighting any chemical fire.

### 6. Accidental release measures

Personal precautions : No smoking.

After spillage and/or leakage : Spill area may be slippery. Dike for recovery or absorb with appropriate material.

Use suitable disposal containers.



# MATERIAL SAFETY DATA SHEET

Page : 2 Revision nr : 2

Date: 5/4/2004

Supersedes: 3/10/2003

11237

# SELECT PETROL & DIESEL 15W50

## 7. Handling and storage

General : No naked flames. No smoking.
Storage : Store in dry, well-ventilated area.

Keep at temperature not exceeding 40°C

Handling : Wash hands and other exposed areas with mild soap and water before eating,

drinking or smoking or when leaving work.

Transport temperature : Keep at temperature not exceeding 40°C

## 8. Exposure controls / personal protection

Personal protection

- Respiratory protection : No special respiratory protection equipment is recommended under normal

conditions of use with adequate ventilation.

- Skin protection : No special clothing/skin protection equipment is recommended under normal

conditions of use.

- Eye protection : Goggles.

- Ingestion : When using, do not eat, drink or smoke.

Industrial hygiene : No special protection required where adequate ventilation is maintained.

Occupational Exposure Limits : 5 mg/m3 for oil mists (TWA, 8h-workday) recommended, based upon the ACGIH

TLV (Analysis according to US NIOSH Method 5026, NIOSH Manual of Analytical

Methods, 3rd Edition).

#### 9. Physical and chemical properties

Physical state : Oily liquid.
Colour : Yellow-brown.

Odour : Oil.

pH value : Not applicable.

Density [g/dm³] : 882

Vapour density (101.3 kPa/air=1) : >12

Viscosity at 40°C [mm2/s] : 135

Solubility in water : Negligible.

Flash point [°C] (ASTM D 92) : >235

Auto-ignition temperature [°C] : No data available.

Explosion limits (vol% in air) : LEL: 1.0 UEL: 6.0

Log P octanol / water at 20°C : No data available.

## 10. Stability and reactivity

Hazardous decomposition products : None under normal conditions. Hazardous reactions : None under normal conditions.

Hazardous reactions : None under normal conditions. Hazardous properties : None under normal conditions.

Materials to avoid : Strong oxidizers.

Acids. Bases.

#### 11. Toxicological information

Inhalation : Neglegible hazard at ambient/normal handling temperatues.

Elevated temperatures or mechanical action may form vapours, mists, or fumes,

which may be irritating to the nose, throat and lungs.

Skin contact : Repeated or prolonged skin contact may cause irritation.

Eye contact : Slightly irritant, does not damage eye tissue

Ingestion : Low level of acute/systematic toxicity.

Minute amounts aspirated into the lungs during ingestion or vomiting may cause



# MATERIAL SAFETY DATA SHEET

Page : 3
Revision nr : 2

Date: 5/4/2004 Supersedes: 3/10/2003

11237

# **SELECT PETROL & DIESEL 15W50**

## 11. Toxicological information (continued)

severe pulmonary injury and death.

#### 12. Ecological information

Persistence and degradability
 Not soluble in water, so only minimally biodegradable.

#### 13. Disposal considerations

Disposal : Dispose in a safe manner in accordance with local/national regulations.

## 14. Transport information

General information : Not regulated.

#### 15. Regulatory information

Symbol(s) : None.
R Phrase(s) : None.
S Phrase(s) : None.

\* Safety advises : Contains : LOB Calcium long chain alkarylsulphonate. May produce an allergic

reaction.

#### 16. Other information

Text of R-Phrases in § 2 : R53 - May cause long-term adverse effects in the aquatic environment.

Further information : Revision - See : \*

Print date : 5/4/2004

DISCLAIMER OF LIABILITY The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document

Antipoison Center - tel: +32 (0)70 245 245