

5w30 Supreme Plus Longlife



Description.

ACDelco Supreme Plus Longlife is an engine oil of the latest generation, based on carefully selected non-conventional base oils for the lubrication of modern gasoline and diesel engines with turbo and that allows extended oil drain intervals.

Advantages

This oil provides excellent fluidity at low temperature which means low resistance during start. Its exceptional viscosity index gives very high thermal stability resulting in a leading fuel economy formulation.

SPECIFICATIONS;

API SL/CF	Opel B-040-2095
ACEA A3-02/B3-98#2	Opel B-040-2098
B4-02/A3/B4-04	
GM LL-A-025 / LL-B-025	

APPLICATIONS;

4-stroke gasoline engines, multi-valves, turbo with extended drain intervals
4-stroke diesel engines, with or without turbo with extended drain intervals

TYPICAL CHARACTERISTICS;

Test	Method	Unit	Average result
SAE-class			5W30
Density at 15°C	D 4052	kg / m ³	855
Viscosity at 40°C	D 445	cSt	69
Viscosity at 100°C	D 445	cSt	11.7
Viscosity index	D 2270		166
Flash point COC	D 92	°C	232
Pour point	D 97	°C	-39
TBN	D 2896	g KOH/kg	10.5
Sulphated ash	D 874	mass %	1,35
Loss by evaporation	NOACK	mass %	11.3